NOMA® THERM 3 mm









NOMA® THERM is a thermal wall insulation panel made of polystyrene and laminated with a carton layer.

Product features:

- Heats rooms faster
- Saves heating costs
- Improves the living environment
- Increases wall surface temperature
- Creates an ideal background for wallpapers
- Overlaps unevenesses











we will succeed together



Gert-Noël-Strasse – B-4731 Eynatten **(** +32 87 85 85 00 − **(** +32 87 85 85 11)

info@nmc.eu



NOMA® THERM 3 mm



Technical data:

Material:	Composite of EPS (expanded polystyrene) and cardboard	
Thickness:	3 mm	
Thermal resistance:	0,071 m ² K / W at 10°C	
Insulation effect:	17% less heat loss *	
Temperature resistance:	Up to + 75 ° C	
Fire classification:	Euroclass E according to EN 13501-1 (if used on incombustible mineral substrates of Euroclasses A1 or A2 s1d0 or on wooden based substrates with a density of at least 300 kg/m³)	
Glue consumption:	± 350 g/m ² DECOFIT	

^{*} Regarding to a wall thickness of 23cm

Application:

- The substrate must be clean and dry;
- The stripes can be cut with scissors or a cutter. The carton layer must be cut a little longer than the polystyrene layer;
- Apply DECOFIT P adhesive on the width of the wall with a 2.5 mm toothed spatula;
- Apply the cut lengths with the polystyrene side against the wall, fix edge-to-edge. Align and press well with a plastic spatula or a rubber roller;
- Cover the joints with NOMA® FIX joint cover tape;
- Let it dry for 24 to 48 hours;
- NOMA ® THERM 3mm cannot be painted.

Range of products::

Туре	Width m	Length m	Thickness mm	Packaging Unit
3 mm	0,5	10	3	8 rolls / box